

# PAINTING HOSES

Professional range of hoses specific to paint booths, also available in the practical 10 /12 metre coupled versions.

In addition to the high performance Polyurethane and flexible Ragno, already popular and appreciated on the market, a new Walcom® SUPERFLEX hose is introduced with high performance in terms of sturdiness, durability, seal, temperature resistance and flexibility: ideal for safe painting in the spray booth.

## HOSES

ITEM ID DESCRIPTION

### SUPERFLEX

**60307** High performance and resistance hose, PU (Polyurethane) composite and thermoplastic rubber, reinforced with polyester. Antistatic. **100 m coil**  
Internal diameter 10 mm - external diameter 15 mm

Substrate and cover: PU composite and thermoplastic rubber

Reinforcing: polyester fiber

Operating air pressure: 15 - 20 bar / 217 - 290 psi

Exploding pressure: 60 bar / 870 psi

Temperature: - 15°C + 70°C

Packaging: 1 pcs



### SUPERFLEX WITH FITTINGS

**60309** High performance and resistance hose, PU (Polyurethane) composite and thermoplastic rubber, reinforced with polyester. Antistatic. **12 m coil**  
Internal diameter 10 mm - external diameter 15 mm

Substrate and cover: PU composite and thermoplastic rubber

Reinforcing: polyester fiber

Operating air pressure: 15 - 20 bar / 217 - 290 psi

Exploding pressure: 60 bar / 870 psi

Temperature: - 15°C + 70°C

Packaging: 1 pcs



### HF - SUPERFLEX WITH FITTINGS

**60309/HF** High performance and resistance hose, PU (Polyurethane) composite and thermoplastic rubber, reinforced with polyester. Antistatic. **12 m coil**  
Internal diameter 10 mm - external diameter 15 mm

Substrate and cover: PU composite and thermoplastic rubber

Reinforcing: polyester fiber

Operating air pressure: 15 - 20 bar / 217 - 290 psi

Exploding pressure: 60 bar / 870 psi

Temperature: - 15°C + 70°C

Standard HF connection

Packaging: 1 pcs



### STRAIGHT POLYURETHANE

**60200** **100 m coil**  
Internal diameter 6 mm - external diameter 10 mm

**60201** **100 m coil**  
Internal diameter 8 mm - external diameter 12 mm

**60202** **100 m coil**  
Internal diameter 10 mm - external diameter 14.5 mm

Substrate and cover: 100% polyurethane

Reinforcement: 550/1100 Trevira Heochst polyester yarn

Operating air pressure: 20 bar / 290 psi

Exploding pressure: 60 bar / 870 psi

Temperature: - 25°C + 60°C

Packaging: 1 pcs

