

PAINTING HOSES

HOSES

ITEM ID DESCRIPTION

STRAIGHT POLYURETHANE WITH FITTINGS

60210 10 m coil with 2 swiveling female 1/4" fittings
Internal diameter 6 mm - external diameter 10 mm

60211 10 m coil with 2 swiveling female 1/4" fittings
Internal diameter 8 mm - external diameter 12 mm

60212 10 m coil with 2 swiveling female 1/4" fittings
Internal diameter 10 mm - external diameter 14.5 mm

Substrate and cover: 100% polyurethane

Reinforcement: 550/1100 Trevira Hoechst polyester yarn

Operating air pressure: 20 bar / 290 psi

Exploding pressure: 60 bar / 870 psi

Temperature: - 25°C + 60°C

Packaging: 1 pcs



STRAIGHT POLYURETHANE WITH FITTINGS

60220 25 m coil with 2 swiveling female 1/4" fittings.
Internal diameter 6 mm - external diameter 10 mm

60221 25 m coil with 2 swiveling female 1/4" fittings.
Internal diameter 8 mm - external diameter 12 mm

60222 25 m coil with 2 swiveling female 1/4" fittings.
Internal diameter 10 mm - external diameter 14.5 mm

Substrate and cover: 100% polyurethane

Reinforcement: 550/1100 Trevira Hoechst polyester yarn

Operating air pressure: 20 bar / 290 psi

Exploding pressure: 60 bar / 870 psi

Temperature: - 25°C + 60°C

Packaging: 1 pcs



RAGNO HOSE

60250 50 m coil
Internal diameter 10 mm - external diameter 15 mm

60254 50 m coil
Internal diameter 8 mm - external diameter 12 mm

Substrate and cover: polyurethane anti-abrasive and thermoplastic rubber

Reinforcement: polyester yarn

Operating air pressure: 20 bar / 290 psi

Exploding pressure: 60 bar / 870 psi

Temperature: - 20°C + 60°C

Packaging: 1 pcs



RAGNO HOSE WITH FITTINGS

60252 10 m coil with fittings
Internal diameter 10 mm - external diameter 15 mm

Substrate and cover: polyurethane anti-abrasive and thermoplastic rubber

Reinforcement: polyester yarn

Operating air pressure: 20 bar / 290 psi

Exploding pressure: 60 bar / 870 psi

Temperature: - 20°C + 60°C

Packaging: 1 pcs

