TYPE | ITEM ID | RECOMMENDED USE

FSRD 4

A modular filter system ideal for use in the painting booth. **Ref. 60138/11**

- Central body: anodized aluminum
- Composition: 1) Pre-filtering element in sythentic fibre for the elimination of condensation. Automatic discharge.
  2) Oil-separating filter for the elimination of residual pollutants. Manual drainage tap.
  3) Silica dryer group to reduce residual humidity in the compressed air. Nr. 3 saturation indicator lights.
  4) Active carbon filter to eliminate all impurities and obtain breathable air. Max oil residue < 0.0003 mg/m^3.
- Pressure adjuster: membrane system and automatic decompression
- Air inlet: F 3/4"; air outlet: n° 2 from M 1/4"
- Filtering power: air 5 µ - oil 0.01 µ
- Operating air pressure: 12 bar
- Air consumption: 1200 l/min. to 6 bar
- Weight: 11 Kg



FSRD 3

A modular filter system ideal for use in the painting booth. **Ref. 60123/11**

- Central body: anodized aluminum
- Composition: 1) Pre-filtering element in sythentic fibre for the elimination of condensation. Automatic discharge.
  2) Oil-separating filter for the elimination of residual pollutants. Manual drainage tap.
  3) Silica dryer group to reduce residual humidity in the compressed air. Nr. 3 saturation indicator lights.
  4) Filter to eliminate dust generated by silica, 5 µ filtering capacity.
- Pressure adjuster: membrane system and automatic decompression
- Air inlet: F 3/4"; air outlet: n° 2 from M 1/4"
- Filtering power: air 5 µ - oil 0.01 µ
- Operating air pressure: 12 bar
- Air consumption: 1200 l/min. to 6 bar
- Weight: 11 Kg



FSRD 2

A modular filter system ideal for use in the painting booth. **Ref. 60145/11**

- Central body: anodized aluminum
- Composition: 1) Pre-filtering element in sythentic fibre for the elimination of condensation. Automatic discharge.
  2) Oil-separating filter for the elimination of residual pollutants. Manual drainage tap.
  3) Active carbon filter to eliminate all impurities and obtain breathable air. Max oil residue < 0.0003 mg/m^3.
- Pressure adjuster: membrane system and automatic decompression
- Air inlet: F 3/4"; air outlet: n° 2 from M 1/4"
- Filtering power: air 5 µ - oil 0.01 µ
- Operating air pressure: 12 bar
- Air consumption: 1200 l/min. to 6 bar
- Weight: 7 Kg

